

The lottery terminal made in Austria Fast - Accurate - Reliable

Because of its speed and precision, the self-service lottery terminal is the solution for medium to high betting slip volumes. Rapid identification, evaluation and processing of betting slips avoids long waiting lines.

High-quality embedded industry PC components enable adaptation to specific customer needs. Upgrades in the event of technical advancements are possible at all times as needed, without any additional development costs. This means maximum investment security.

We offer

- High speed and precision of the scanner and printer (identification, evaluation and further processing)
- Maximum reliability and availability
- Processing of betting slips in all conventional formats
- Full-surface scanning and OCR/OMR evaluation permit the flexible selection of betting slip formats and the rapid introduction of new games. No double readings.
- The use of high-quality embedded industry PC components offers excellent expandability, ensuring a sound, future-proof investment.
- Ergonomically sophisticated design allowing maximum user friendliness and accessibility.
- Open system architecture which enables the use of various operating systems and the connection to different central systems

Expandable

The basic functionality can be adapted to special customer needs.

The housing colors can be freely selected and can be adapted to the corporate design of the lottery company. The customer software is open configurable.



Technical data Lottery terminal

Access

Frontload

Installation

Free-standing

Features

- Case color: Body RAL selectable, front panel RAL selectable / stainless steel, footplate RAL selectable / stainless steel
- Control panel: embedded industry panel PC (can be configured individually with TPM & secure boot)
- 23.8" full HD (1920 x 1080) multi-touch screen (PCAP touch)
- 1D/2D barcode scanner
- JCM bill reader
- CCV payment system: vandalism-resistant stainless steel keyboard / high-secure card reader / contactless card reader (NFC)
- CPI coin depositing mechanism
- Lottery ticket scanner
- Custom TICKET printer with brander up to 82.5 mm
- WLAN 2.4 + 5 GHz
- Various monitored lock options

Optional features

- Monitor attachment 23.8" full HD (1920 x 1080)
- Uninterruptible power supply
- Braille pictograms
- Customer-specific color schemes for cases

Power supply

230V +/- 10%, 50 Hz +/- 10%

Environmental conditions

- Operating temperature: 0°C to +40°C
- Relative humidity: 15% to 80%

Dimensions / weight

- Width 640 mm, depth 520 mm, height 1590 mm (2020 mm with monitor attachment)
- Approx. 200 kg

Accessibility

Meets usual accessibility standards:
EN301549 / ADA2010

System software

- Operating system: Windows 7 / 10 / Windows 10 IoT / Linux (Ubuntu)
- Freely configurable customer software



optionally with monitor attachment